



RCJYZ Standoff Insulator M10

Series: M10

Insulation material using flame retardant (UL94V-0) high strength, excellent electrical properties of plastic;

There are three types of copper, aluminum and steel inserts to choose from;

Used in power supply or cabinet to play the role of insulation and support for live parts;

Insulation resistance greater than 500MΩ;

Working temperature: -30 °C ~ 120 °C

According to customer requirements assembly screw;

Can be customized according to customer requirements of different colors;

Customers can request a variety of customized products.

RCJYZ Standoff Insulator RCJYZ Standoff Insulator M10

Specification

Item No.	Thread	External Sizes (mm) (OD*H)	Rated Voltage (V)	Withstand Voltage (V/min)	Max Thread Screw Moment (Kgf.cm)	Insulate Material	Color	Insert material
RCJYZ-09	M10x14.5	47.1x50	1500	5000	350	BMC	Red	Copper
RCJYZ-18	M10x10	34Xφ30.3	1500	5000	305	PF	Red	Copper
RCJYZ-19	M10x11	Φ36x34.3	1500	5000	305	PF	Red	Copper
RCJYZ-24D	M10X18	Φ33x45	1500	10000	300	BMC	Red	Copper
RCJYZ-51	M10X1.75x17	Φ45x51	600	3000	100	BMC	Red	Copper
RCJYZ-54	M10X18	Φ44.5x50.8	1500	5000	500	PF	Red	Copper
RCJYZ-54B	M10X18	Φ45*51	1000	3000	678	BMC	Red	Copper
RCJYZ-124A	M10x12	Φ41*35	600	5000	124	BMC	Grey	Copper

Product Show



